



EJ-701DR Plus

Diversity receiver, 16 channels,
863-865MHz

Features

- 1 receiver
- Wireless coverage up to 100 m
- Digital display
- Diversity reception
- ½ width 19" rack mountable
- The receiver is connected to the existing sound system and/or to a hearing loop driver.
- Scan mode for channel search
- Sync mode for automatic synchronisation
- Balanced XLR connectors and unbalanced 6.3mm jack

Modular Microphone System Range.

The EJ-701DR Plus wireless receiver is part of the OKAYO II modular wireless system range. The diversity receiver can be used with one wireless microphone and connects to existing sound system and/or hearing loop driver.

With this wide range of options, the OKAYO II wireless microphone system is uniquely flexible and can be easily configured for different applications. It is equally suitable for use in schools, seminars, meetings, places of worship, product demonstrations, aerobics classes and guided tours.

In addition to the EJ-701DR Plus, the OKAYO II modular microphone system range includes push to talk microphones, body pack transmitters with a range of microphone options, body pack receivers, and rechargeable powered speakers with built in receivers.

Univox – co-developed with OKAYO

Univox and Okayo have co-developed body pack transmitters and receivers to improve speech intelligibility for hearing aid users. To comply with accessibility requirements and provide a good audio experience even for the hearing impaired, make sure you use these special developed products.

Specifications

EJ-701DR Plus, Diversity receiver

2 x 16 channel receivers

Carrier frequency	863-865 MHz, other frequencies on demand
Channels	16 (frequency dependant)
Wireless coverage	up to 100 m (free field)
LCD window	channel, reception strength
Channel adjustment	frequency set, up/down
Frequency modulation	max. 24 MHz
Dynamic range	110 dB
T.H.D	<0.5 %
Pre-emphasis	<50 μ S
Frequency response	70 Hz - 17 KHz
Antenna	diversity fixed antenna x 2
Audio output	6.3 mm (mixer) XLR balanced
Output level	6.3mm: Hi: 700mV/Low: 70mV XLR:1V
Power supply	AC switching power adapter 100 ~ 240V, 12 ~ 15V/0.6A
Weight	1.2 kg
Dimensions (DxWxH)	210 x 215 x 44mm
Part. No.	506701+



For complete manual and system components, please refer to univox.eu.

